

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 April 2004 (15.04.2004)

PCT

(10) International Publication Number
WO 2004/030877 A1

(51) International Patent Classification:
B23P 15/40, B29C 47/02, B32B 31/30

B26F 1/44,

(74) Agent: URQUHART-DYKES & LORD; Tower House,
Merrion Way, Leeds LS2 8PA (GB).

(21) International Application Number:
PCT/GB2003/003835

(22) International Filing Date:
4 September 2003 (04.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0223147.0 5 October 2002 (05.10.2002) GB

(71) Applicant (for all designated States except US): MAN
MAT LIMITED [GB/GB]; Matrix House, Ballthane In-
dustrial Park, Ballasalla IM9 2AJ (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SNODGRASS, Fran-
cis, Matllage [GB/GB]; 527 Clifton Drive North, Lytham
St. Annes, Lancashire FY8 2QU (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: MATRIX ASSEMBLY



(57) Abstract: A method of forming a matrix assembly is disclosed which comprises providing a steel strip (10), treating the upper surface of the steel strip with a resin adhesive, extruding one or more plastic material strips (24, 26) onto the metal strip to define a longitudinal channel (28) and heating the assembly so formed to cure the resin adhesive and adhere the plastic material to the metal strip. The method of the invention obviates the need to perforate the metal strip and this leads to a number of advantages. Firstly, omitting the perforation step enables the matrix assembly to be produced more cheaply. Secondly, with there being no perforations present, it is possible to use a thinner steel strip (for example, of thickness of 0.002") and still retain adequate strength. This means that no modification need be made to the height of the creasing dies in a cutting and creasing press.